

INVERTED CULVERTS & LIDS

A practical solution for housing underground cables and conduits in a variety of construction projects including data centres, water treatment plants, sub stations, etc. This engineered product is available in a range of standard sizes and reduces construction times.

Lids are custom fabricated to suit project requirements.



SPAN TABLE		SPAN (mm)												
		300	450	600	900	1200	1500	1800	2100	2400	2700	3000	3300	3600
DEPTH (mm)	225	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	300	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	450		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	600			✓	✓	✓	✓	✓	✓	✓	✓	^	^	^
	750				✓	✓	✓	✓	✓	✓	✓	^	^	^
	900				✓	✓	✓	✓	✓	✓	✓	✓	^	^
	1200					✓	✓	✓	✓	✓	✓	✓	✓	^
	1500						✓	✓	✓	✓	✓	✓	✓	✓
	1800							✓	✓	✓	✓	✓	✓	✓
	2100								✓	✓	✓	✓	✓	✓
	2400									✓	✓	✓	✓	✓
	2700										✓	✓	✓	✓
	3000											✓	✓	✓
	3300												✓	✓
	3600													✓

*Leg thickness varies according to the height of the culvert. Drawings of required sizes are available upon request. Designed & Manufactured to AS1597. Where design requirements are outside of or greater than the parameters of AS1597, structural design and detailing to be provided by project engineer.

^Custom upon request